


耐熱電纜 (380°C/15min)

參考圖



- 規格 【HR-CV】耐熱電線電纜認可基準
- 用途 適用於額定電壓600V以下之消防安全設備或緊急供電系統之控制回路用線。
- 特性 具有良好耐熱、耐水、耐化學藥品、耐磨、耐龜裂...等特性，重量輕易敷設及終端處理簡單。

構造、性能表 / 600V

導體直徑 或標稱截面積	芯線數	導體		絕緣 厚度	被覆 厚度	完成外徑 (約)	最大導體 電阻		最小絕緣電阻		試驗電壓
		構成	外徑 (約)				20°C	20°C	75°C	A.C.	
mm/mm ²		No./mm	mm	mm	mm	mm	Ω/km	MΩ-km		V/1min	
1.2mm	1C	1/1.2	1.2	0.50	0.50	3.2	16.0	50	0.05	1500	
	2C			0.50	0.90	6.2					
	3C			0.50	0.90	6.5					
	4C			0.50	0.90	7.1					
	5C			0.50	0.90	7.8					
	6C			0.50	0.90	8.5					
	7C			0.50	0.90	8.5					
	8C			0.50	0.90	9.1					
	10C			0.50	0.90	10.7					
	12C			0.50	1.00	11.2					
	16C			0.50	1.00	12.4					
	18C			0.50	1.00	13.1					
	20C			0.50	1.00	13.7					
	24C			0.50	1.10	15.5					
30C	0.50	1.20	16.6								
1.6mm	1C	1/1.6	1.6	0.50	0.50	3.6	9.01	50	0.05	1500	
	2C			0.50	0.90	7.0					
	3C			0.50	0.90	7.4					
	4C			0.50	0.90	8.1					
	5C			0.50	0.90	8.9					
	6C			0.50	0.90	9.7					
	7C			0.50	0.90	9.7					
	8C			0.50	0.90	10.4					
	10C			0.50	1.00	12.5					
	12C			0.50	1.00	12.9					
	16C			0.50	1.00	14.3					
	18C			0.50	1.00	15.1					
	20C			0.50	1.00	15.8					
	24C			0.50	1.30	18.3					
30C	0.50	1.30	19.3								
2.0mm	1C	1/2.0	2.0	0.50	0.50	4.0	5.77	50	0.05	1500	
	2C			0.50	0.90	7.8					
	3C			0.50	0.90	8.3					
	4C			0.50	0.90	9.0					
	5C			0.50	0.90	10.0					
	6C			0.50	0.90	10.9					
	7C			0.50	0.90	10.9					
	8C			0.50	1.00	12.0					
	10C			0.50	1.00	14.1					
	12C			0.50	1.00	14.5					
	16C			0.50	1.00	16.2					
	18C			0.50	1.00	17.1					
	20C			0.50	1.20	18.4					
	24C			0.50	1.30	20.7					
30C	0.50	1.30	21.9								
1.25mm ²	1C	7/0.45	1.35	0.60	0.50	3.6	16.8	50	0.05	1500	
	2C			0.60	1.00	7.1					
	3C			0.60	1.00	7.5					
	4C			0.60	1.00	8.2					
	5C			0.60	1.00	8.9					
	6C			0.60	1.00	9.7					
	7C			0.60	1.00	9.7					
	8C			0.60	1.00	10.5					
	10C			0.60	1.00	12.3					
	12C			0.60	1.00	12.6					
	16C			0.60	1.00	14.0					
	18C			0.60	1.00	14.8					
	20C			0.60	1.20	16.0					
	24C			0.60	1.30	18.0					
30C	0.60	1.40	19.2								
2mm ²	1C	7/0.6	1.8	0.60	0.50	4.0	9.43	50	0.05	1500	
	2C			0.60	1.00	8.0					
	3C			0.60	1.00	8.5					
	4C			0.60	1.00	9.2					
	5C			0.60	1.00	10.2					
	6C			0.60	1.00	11.1					
	7C			0.60	1.00	11.1					
	8C			0.60	1.00	12.0					
	10C			0.60	1.00	14.1					
	12C			0.60	1.00	14.5					
	16C			0.60	1.00	16.2					
	18C			0.60	1.00	17.1					
	20C			0.60	1.20	18.4					
	24C			0.60	1.50	21.1					
30C	0.60	1.50	22.3								



宏泰電工股份有限公司

HONG TAI ELECTRIC INDUSTRIAL CO., LTD.

總公司：台北市敦化南路二段 65 號 20 樓
 觀音廠：桃園市觀音區國建一路 2 號
 台中營業處：台中市清水區四維東路 500 號
 佳里營運處：台南市佳里區文化西路 615 號
 高雄聯絡處：高雄市苓雅區光華一路 206 號 12 樓之 6
 Website: www.hong-tai.com.tw

TEL: (02)2701-1000 / FAX: (02)2708-1100
 TEL: (03)483-7266 / FAX: (03)483-0630
 TEL: (04)2656-6571 / FAX: (04)2656-6572
 TEL: (06)722-7999 / FAX: (06)722-7977
 TEL: (07)227-1552~3 / FAX: (07)227-1841
 E-mail: p-sale@hong-tai.com.tw